

Tennant 7100

A compact scrubber-dryer, packed with industrial cleaning strength and available with FaST (Foam Scrubbing Technology) it cleans up to 5,700 m² an hour. The 7100 is narrow enough to scrub through 90cm doorways and can turn in a 1.84m aisle. Highly manoeuvrable, extremely comfortable and productivity is increased up to 30% over walk-behind scrubbing. Available with disc brushes or cylindrical brushes.



Features


- The high rpm of the brushes, brush pressure and vacuum in combination with working speed gives excellent performance
- FaST (Foam Scrubbing Technology)
- Cylindrical scrub system
- ES (water recycling system)
- Memorised, ergonomical one button scrubbing

Benefits


- Excellent performance
- Up to 30% more productivity, up to 30% cost saving and 95% savings on water and detergent
- Cylindrical brushes pick up occasional debris to eliminate the need for sweeping before scrubbing
- Extends runtime and increases productivity for medium to heavy soilage
- For ease and comfort

Applications


- Warehousing & distribution facilities
- Transport sector
- Manufacturing & production facilities
- Contract cleaning




Scrubs through doorways



Front tire for increased manoeuvrability



Convenient drain hoses



Machine in action



TECHNICAL SPECIFICATIONS 7100

		70cm	80cm
Machine Dimensions			
Working width (scrubbing path)	cm	70	80
Squeegee width	cm	85	102
Dimensions (l x w x h)	cm	169x85x137	169x85x137
Machine weight, (net)	kg	385	385
Scrubbing System			
Area coverage - theoretical (max)	m ² /h	5,040	5,760
Area coverage - practical (max)	m ² /h	3,000	3,500
Number of brushes/pads	qty	2	2
Diameter disc brush/pad	cm	36	41
Length cylindrical brush x dia	cm	71 x 15	81 x 15
Brush assist drive	yes/no	no	no
Transaxle drive	yes/no	yes	yes
Brush pressure (disc only)	g/cm ²	0-59	0-45
Brush pressure	kg	0-90	0-90
Recovery System			
Airflow	l/s	36	36
Water lift	kPa	18	18
Practical capacity solution tank	L	114	114
Practical capacity recovery tank	L	114	114
Power			
Power source		battery 36V	battery 36V
Total power consumption	W	2,920 STD 2,990 FaST+ES	2,920 STD 2,990 FaST+ES
Protection class	I/II/III	III	III
Sound level	dB(A)	75	75
Operation			
ES	yes/no	yes	yes
FaST	yes/no	yes	yes
Cylindrical/Disc		cylindrical or disc	cylindrical or disc
Propelling			
Transport speed	km/h	7.2	7.2
Working speed	km/h	5	5
Reverse	km/h		
Climbing capacity	%	14	14
Turning circle	cm	185	185

Configuration

- 70cm disc or cylindrical Standard
- 70cm disc or cylindrical ES
- 70cm disc or cylindrical FaST
- 80cm disc or cylindrical Standard
- 80cm disc or cylindrical ES
- 80cm disc or cylindrical FaST

The above mentioned configuration includes as standard head lights, flashing lights, backup alarm as well as one FaST-PAK™ on the FaST model.

Accessories


- Brushes (disc or cylindrical) • Pads • Pad drivers • Batteries • Charger • Conventional detergent or FaST

Options

- Power wand (not on FaST models)

Warranty

24 Months (or max 2000 running hours) on parts and 12 months (or max 1000 running hours) on labour, whichever comes first, excluding wear items.



994991-10/04

TENNANT NV
 Industrielaan 6, 5405 AB Uden
 P.O. Box 6 5400 AA Uden
 THE NETHERLANDS
 Tel: 00800-2255 8366
 Fax: 00800-3298 3662
 E-mail: europe@tennantco.com
 www.tennantco.com

WALTER-BROADLEY MACHINES Ltd.,
 a Tennant company
 Gladstone Road Northampton NN5 7RX
 UNITED KINGDOM
 Tel: 00800-2255 8366
 Fax: 00800-3298 3662
 Tel (local rate UK only): 01604 583191
 E-mail: europe@tennantco.com



Creating a cleaner, safer world™